Vellum / RA678 / GA 62

Facestock

Vellum

Description Calendered uncoated woodfree paper.

- Color White
- Finish Matt

Applications Ideal for all types of applications: variable label information (barcodes, expiry date, price, weight etc.)

Printing techniques Suitable for printing on flexo (all types), conventional offset, offset UV, Dry toner, thermal transfer.

| Property | Norm | Units | Value | Tolerance |
|------------------------|------------|-------|-------|-----------|
| Substance | ISO 536 | g/m2 | 68 | ± 5 |
| Thickness | ISO 534 | μm | 65 | ± 2 |
| Whiteness CIE | ISO 11475 | % | 152 | ± 5 |
| Opacity | ISO 2471 | % | 86 | -2 |
| Tensile strength MD/CD | ISO 1924-2 | kN/m | 4 / 2 | -1 |

Adhesive

RA678

Description Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces.

| Shelf life From the date of manufacture 1 y | year in 20°C and RH 50% |
|---|-------------------------|
|---|-------------------------|

| Tolerance |
|-----------|
| 1 - 2,9 |
| 0,7 - 1,7 |
| ≥ 60 |
| |
| |
| |
| |

Liner

Glassine Ambar 62

Super-calendered translucent glassine paper especially designed for automatic labelling Description applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Yellow

| Property | Norm | Units | Value | Tolerance |
|-----------|---------|-------|-------|-----------|
| Substance | ISO 536 | g/m² | 56 | 55-57 |
| Thickness | ISO 534 | μ | 48 | 46 - 49 |

Values are subject to change without notice. Last updated 01/01/2025.

* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.