

Thermal Eco BPA Free / CE432 / BG50

Facestock

Thermal Eco BPA Free

Description Non top-coated standard sensitive paper without Bisphenol A.

Color White

Applications Variable information labelling in dry environments such as POS price marking and barcodes generally for shipping forms, logistics and dispatch.

Printing techniques Suitable for printing on flexo (all types), offset UV.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	70	± 4%
Thickness	ISO 534	µm	78	± 3
Bekk smoothness	ISO 5627	s	325	≥ 200 / ≥ 150
Whiteness CIE	ISO 11475	%	122	± 6
Tensile strength MD/CD	ISO 1924-2	kN/m	4.9 / 2.2	≥ 0.9

Adhesive

CE432

Description A low tack acrylic semipermanent adhesive that permits repositioning upon application.

Shelf life From the date of manufacture 2 years in +20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	16,7	≥ 12,3
Tack (Quick Stick stainless steel)	FTM 9	N	8,3	≥ 7,4
Shear (1kg, in ² /glass)	FTM 8	min	55	≥ 30
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Glassine Blue 50

Description Super-calendared translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Blue

Applications Predominantly used in applications where a thin liner is needed.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	50	48-52
Thickness	ISO 534	µm	45	42-48

• Values are subject to change without notice. Last updated 01/01/2024.

• The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO

45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.

TECHNICAL SPECIFICATIONS